


30°/30° 10-Port Directional Panel Antenna [617-896, 1695-2690, 3300-4200 and 5150-5925 MHz]

GP2910-06975

Description:

- Single-sector 10-Port MIMO antenna for high capacity stadium and venue applications
- 30°/30° beam width dual-polarized covering 600 MHz/LTE/CELL, AWS/PCS/WCS/BRS, CBRS and LAA / U-NII Bands.
- 2x ports for 617-896 MHz/1695-2690MHz
- 2x ports for 1695-2690 MHz
- 4x ports for 3300-4200 MHz
- 2x ports for 5150-5925 MHz*



617-896, 1695-2690, 3300-4200 and 5150-5925 MHz
10-Port 30x30 Pattern Directional Panel Antenna

*Compliant to 789033 D02 General U-NII Test Procedures New Rules v01r04: The antenna meets current U-NII-1 requirements for gain and upper side-lobe performance. Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - Part 15, Sub-part E

Electrical Specifications

Frequency Range (MHz)	617-698	698-806	806-896	1695-2200	2305-2360	2496-2690	3300-3550	3550-3700	3700-4200	5150-5925
Gain, dBi (max.)	12.5	13.0	13.3	15.5	15.5	16.1	14.6	15.4	16.1	5.5
Gain, dBi (avg.)	12.0	12.3	12.4	13.8	14.6	14.9	14.1	14.7	15.1	4.6
Azimuth Beamwidth (°)	38.6	34.0	29.7	30.9	23.9	21.6	30.2	27.8	24.4	20.7
Elevation Beamwidth (°)	37.3	34.1	31.2	29.5	24.2	20.9	28.0	25.8	23.6	21.2
Front-to-Back Ratio @ 180°, dB (min.)	35	38	39	39	41	41	48	49	47	47
VSWR (max.) / RL (dB, min.)	1.5:1 / 14.0									
Port-to-Port Isolation, dB (min.)	25									
PIM @ 2x20W, dBc (max.)	-153						-145		N/A	
Power per Port, Watts (max.)	200			200			100		1	
Polarization	Dual slant 45° (±45°)									
Impedance	50 Ω									


Mechanical Specifications

Operating Temperature	-40° to 158°F (-40° to +70°C)
Antenna Weight	26 lbs (11.8kg)
Mounting Bracket Weight	5.07 lbs (2.37 kg)
Antenna Dimension (Height x Width x Depth)	29.1" (739.5 mm) x 29.1" (739.5 mm) x 7.1" (179.7 mm)
Input Connector Type	10x 4.3-10(F)
Radome Material	ASA
Radome Color	Gray
RoHS	Compliant
Wind Load, Front (@ 150 km/h)	1809 N / 406 lbf
Wind Load, Side (@ 150 km/h)	466 N / 104 lbf
Wind Load, Maximum (@ 150 km/h)	1862 N / 418 lbf
Ingress Protection	IP65
Wind Survival Rating	150 mph (241 km/h)


Copyright © 2020 – Galtronics Corporation Ltd.

Proprietary Information. All rights reserved. Galtronics reserves the right to modify or amend any antenna or specification without prior notice.

Back Plate Port Configuration/Labeling




Antenna Outline



Antenna Patterns

Horizontal



650 MHz


894 MHz

1990 MHz

3550 MHz

5250 MHz


Vertical



Part Numbers & Ordering Options

Description	Color	Mounting Kit	Part Number
10-Port 30° x 30° Pattern Directional Panel Antenna with 10x 4.3-10 (F) Connectors	Gray	Includes 62-45-09 mounting kit	GP2910-06975-1xx

Mounting Kit and Accessories Part Numbers

Description:	Part Number:
Heavy Duty Mounting Bracket (150 mph) [INCLUDED] The mounting bracket allows wall and pole mounting with flexible and continuous antenna adjustment in the horizontal and vertical plane.	 62-45-09 (Included)
2 Axis Pole/Wall Mounting Bracket (150 mph) [OPTIONAL] Galtronics' mounting bracket offers an easy installation solution to mount Galtronics' stadium antennas to either a pole or a wall. When attaching the antenna to a wall please make sure to select appropriate fasteners (not included).	 62-28-09 (Sold Separately)
Heavy Duty Mounting Bracket (150 mph) [OPTIONAL] This standard mounting bracket offers an easy installation solution to mount the antenna to either a horizontal or a vertical pole.	 MK-07305 (Sold Separately)

Mating Connector Torque:

4.3-10: 3.7 ft-lb (5 Nm)

Copyright © 2020 – Galtronics Corporation Ltd.

Proprietary Information. All rights reserved. Galtronics reserves the right to modify or amend any antenna or specification without prior notice.