



End-of-Life (EOL) Notification

EOL Number: GT4969EOL

Galtronics PEAR™ M4969i Broadband Dual Polarized In-Building Antenna [698-960 MHz, 1710-2700 MHz, 5300-6000 MHz]

Galtronics announces the end-of-sale and end-of-life dates for our referenced model M4969i. The last time to buy the product is July 3, 2020 and the last time to schedule shipments is September 4, 2020 as summarized below:

Notification Date*:	April 17, 2020
Last Time Buy (LTB) Date:	July 3, 2020
Manufacture Discontinuance (MD) Date:	September 4, 2020
End of Life (EOL) Date:	September 4, 2020
Last Time for Order Shipments:	September 4, 2020
Last Time to Repair:	September 4, 2020
Market Regions Affected:	Global
<i>* All orders placed after the date of this notice cannot be canceled or returned. Please check with your Galtronics Sales Representative for details and availability of inventory.</i>	

Reason for End of Life of this Product

Upgraded model PEAR™ GI0801-06971 (1-port SISO) or GI0802-06835 (2-port MIMO) are now available with improved specifications, including 600 MHz and 3500 MHz coverage in smaller physical form factor.

Product Repairs

Product repair or replacement of PEAR™ M4969i will be performed in accordance with existing contractual agreements or customer specific service plans as negotiated prior to EOL or within twelve (12) months of the original purchase date. If beyond Last Time to Repair Date, at Galtronics discretion, replacement model identified below may be provided in lieu of repair.

Galtronics Corporation LTD
8930 S. Beck Avenue, Suite 103 Tempe, Arizona 85284 USA Phone: +1 480-496-5100



Manufacture Discontinuance and Last Time Buy Definition

As part of ending the life of hardware elements this notice serves as a formal communication of Galtronics intent to Manufacture Discontinuance (MD) and offer Last Time Buy (LTB) date for the product(s) noted.

Alternative/Replacement Solution – GI0801-06971 (SISO)

Model Number	Suggested Replacement Model Number*	Specification Comparisons	
		PEAR™ M4969i (discontinued)	PEAR™ GI0801-06971 (SISO replacement model)
PEAR™ M4969i <u>Ordering Options:</u> 02108270-04969U 02108270-04969T	PEAR™ GI0801-06971 <u>Ordering Options:</u> GI0801-06971-112	Specified over 698-960MHz, 1710-2700MHz & 5300-6000MHz	Specified over 617-960MHz, 1695-2690MHz, 3300-4200MHz & 5000-6000MHz
		Uses x2 N-F connectors, one for all frequency bands and second for 1710-2700MHz only	Uses 1x 4.3-10-F DIN connector pigtailed (12"/30 cm long)
		Max. Gain: 2.5/2.4/6.9/7.2/6.0 dBi	Max. Gain: 2.9/6.7/6.4/6.6/7.9 dBi
		VSWR/Return Loss: <1.5:1,14.0dB / <1.7:1,11.8dB / <1.8:1,10.9dB / <2.0:1,9.5dB / 2.5:1. 7.36dB	VSWR/Return Loss: <1.7:1,11.8dB / <1.5:1, 14.0dB / <1.7:1,11.8dB
		Isolation (typ.): 30dB/25dB/25dB/25dB/30dB	Isolation: Not Applicable
		Passive Intermodulation (PIM): ≤-150dBc (2x20W)	Passive Intermodulation (PIM): ≤-153dBc (4.3-10-F type conn.)
		Dimension (DxH): 13.2" (335mm) x 4.88" (124mm)	Dimension (DxH): 8.2" (208mm) x 2.8" (72mm)
		Weight: 1.58 lbs (0.72 Kg)	Weight: 0.90 lbs. (0.41 Kg)

*Galtronics suggests all users verify equivalency for use. Specifications are available from www.galtronics.com



Alternative/Replacement Solution – GI0802-06835 (MIMO)

Model Number	Suggested Replacement Model Number*	Specification Comparisons	
		PEAR™ M4969i (discontinued)	PEAR™ GI0802-06835 (MIMO replacement model)
PEAR™ M4969i <u>Ordering Options:</u> 02108270-04969U 02108270-04969T	PEAR™ GI0802-06835 <u>Ordering Options:</u> GI0802-06835-112	Specified over 698-960MHz, 1710-2700MHz & 5300-6000MHz	Specified over 617-960MHz, 1695-2690MHz, 3300-4200MHz & 5000-6000MHz
		Uses x2 N-F connectors, one for all frequency bands and second for 1710-2700MHz only	Uses 2x 4.3-10-F DIN connector pigtailed (17"/43.2 cm long)
		Max. Gain: 2.5/2.4/6.9/7.2/6.0 dBi	Max. Gain: 3.1/3.6/3.9/4.5/6.0/6.0/5.5/6.8/6.7/9.7 dBi
		VSWR/Return Loss: <1.5:1,14.0dB / <1.7:1,11.8dB / <1.8:1,10.9dB / <2.0:1,9.5dB / 2.5:1. 7.36dB	VSWR/Return Loss: <1.8:1,11.0dB / <1.7:1, 12.0dB
		Isolation (typ.): 30dB/25dB/25dB/25dB/30dB	Isolation (minimum): 12dB/17dB
		Passive Intermodulation (PIM): ≤-150dBc (2x20W)	Passive Intermodulation (PIM): ≤-153dBc (4.3-10-F type conn.)
		Dimension (DxH): 13.2" (335mm) x 4.88" (124mm)	Dimension (DxH): 8.2" (208mm) x 2.8" (72mm)
		Weight: 1.58 lbs (0.72 Kg)	Weight: 0.95 lbs. (0.43 Kg)

Galtronics suggests all users verify equivalency for use. Specifications are available from www.galtronics.com



CUSTOMER ACKNOWLEDGEMENT OF RECEIPT:

Please complete the EOL acknowledgement receipt form below and email it to john.dobiesz@galtronics.com and the Galtronics Contact listed above.

Galtronics will deem this change accepted unless specific conditions of acceptance are provided in writing within 30 days from the date of this notice.

Attention Distributors: Product(s) identified in this notification will become obsolete and as such this EOL notification will act as the official written notification. All obsolete products will be listed in the next published quarterly distributor price book, following an EOL change, and listed on the obsolescence form which accompanies said price book. Within thirty (30) days from the published date of the price book, Distributor shall notify Galtronics in writing of Distributor's then current inventory of the obsolete product.

EOL ACKNOWLEDGEMENT RECEIPT FORM

Company: Contact Name: Title: Date: Email Address: Phone Number: Comments:	
---	--